

VPC-999084

TRANSDUCER SIMULATOR



Description

Model VPC-999084 simplifies the on-line troubleshooting of Dynisco strain gage transducers, signal conditioners, and indicators. Its output can be varied in 20% steps or via a variable trim pot.

Features

- Selectable transducer output sensitivity
- Standard 6 pin Bendix connector
- 5 step linear output 0 − 100%
- Identifies faulty components in a measurement loop
- Simulates a variety of transducers
- Substitutes for most pressure transducers
- Checks indicator linearity
- Diagnostic tool

Performance Characteristics	
Accuracy:	±0.25%each full scale range
Bridge resistance:	Input: 350 Ohms ±2.0% (±5% in variable position)
Full scale output:	Rotary switch selected full scale ranges of: $0.0 \text{ mV/V} \pm 0.25\%$ $1.5 \text{ mV/V} \pm 0.25\%$; $2.0 \text{ mV/V} \pm 0.25\%$; $2.5 \text{ mV/V} \pm 0.25\%$; $3.0 \text{ mV/V} \pm 0.25\%$; $3.3 \text{ mV/V} \pm 0.25\%$; $0 \text{ to } 3.0 \text{ mV/V} \pm 5.0\%$ (variable trim pot)
Configuration:	350 Ohms Wheatstone bridge strain gage
Zero balance:	±0.25% of full scale
Excitation:	15 Vdc, maximum
Electrical connector:	Bendix PT02A - 10 - 6P substitutes for PT46X, MDA46X and DYN-X Series Excitation + Pin C; Signal + Pin A; Excitation - Pin D; Signal - Pin B
Weight:	1 lb.
Note:	Each output range has calibrated steps of 20%, 40%, 60%, 80% and 100% of selected mV/V range. A variable position permits continuous adjustment from 0% to 100% of 3 mV/V ±5.0%

To Order

Specify PN VPC-999084. Optional 1ft Adapter Cable to simulate 8 pin PT420/MDT420 series transducer connector also available, PN 800860

Delivery

Please call for specific delivery information.



©2016. Dynisco reserves the right to make changes without notice.
Refer to www.dynisco.com for access to Operator Manual and other support documentation.
DSVPC4999084
Rev: 1206

Dynisco

38 Forge Parkway Franklin, MA 02038 USA

Email infoinst@dynisco.com

+86 21 34074025